



INTENDED USE	Means of personal fall protection
MATERIAL	Stainless steel 1.4301
CERTIFICATION	According to ČSN EN 795:2013 (1 person) and according to ČSN P CEN/TS 16415:2013 (up to 4 people)
POINT ACCESSORIES	1× ANCHOR EYE, 1× Nut M16 SELF-LOCKING, Label
NOMINAL HEIGHT OF THE ANCHOR POINT	200 mm – marking 18-200
	300 mm – marking 18-300
	400 mm – marking 18-400
	500 mm – marking 18-500
	600 mm – marking 18-600
	700 mm – marking 18-700
DETERMINING THE HEIGHT OF THE ANCHOR POINT	800 mm – marking 18-800
	900 mm – marking 18-900
	1000 mm – marking 18-1000
DETERMINING THE HEIGHT OF THE ANCHOR POINT	Nominal height of the anchor point = Height of the roof structure + 100 to 200 mm
MANUFACTURER	Axel Group s.r.o
TIGHTENING TORQUES	Self-locking nut M16: do not tighten, anchor eye rotates freely with minimal play
	Screw M10 or M12 strength 8.8: Tightening torque 30 Nm
RECOMMENDED FASTENERS	You can use M10 screws, strength 8.8 and higher, M12 screws, strength 5.8 and higher, according to the steel profiles used, the recommended spacing of the holes and the size of the holes in them