



INTENDED USE	Means of personal fall protection
MATERIAL	Stainless steel 1.4301
CERTIFICATION	According to ČSN EN 795:2013 (1 person) and according to ČSN P CEN/TS 16415:2013 (up to 4 people)
PART OF THE DELIVERY	1× ANCHOR EYE, 1× Nut M16 SELF-LOCKING, 4× Folding anchor Axel Safety M10, Label
NOMINAL HEIGHT OF THE ANCHOR POINT	200 mm – marking 18-200
	300 mm – marking 18-300
	400 mm – marking 18-400
	500 mm – marking 18-500
	600 mm – marking 18-600
	700 mm – marking 18-700
DETERMINING THE HEIGHT OF THE ANCHOR POINT	800 mm – marking 18-800
	900 mm – marking 18-900
	1000 mm – marking 18-1000
MANUFACTURER	Nominal height of the anchor point = Height of the roof structure + 100 to 200 mm
TIGHTENING TORQUES	Self-locking nut M16: do not tighten, anchor eye rotates freely with minimal play
HOLES FOR THE ANCHOR IN THE TRAPEZOIDAL SHEET	Folding anchor M10: tightening torque 30 Nm
	To push the anchor through the trapezoidal sheet, it is necessary to drill 4 holes with a diameter of 29 – see assembly instructions