



INTENDED USE	Means of personal fall protection
MATERIAL	Stainless steel 1.4301
CERTIFICATION	According to ČSN EN 795:2013 (1 person) and according to ČSN P CEN/TS 16415:2013 (up to 4 people)
PART OF THE DELIVERY	1× ANCHOR EYE, 1× Nut M16 SELF-LOCKING, Label
NOMINAL HEIGHT OF THE ANCHOR POINT	200 mm-designation 34-200
	300 mm-designation 34-300
	400 mm-designation 34-400
	500 mm-designation 34-500
	600 mm-designation 34-600
700 mm-designation 34-700	
DETERMINING THE HEIGHT OF THE ANCHOR POINT	Nominal height of the anchor point = Height of the roof structure + 100 to 200 mm
MANUFACTURER	Axel Group s.r.o
TIGHTENING TORQUES	Self-locking nut M16: do not tighten, anchor eye rotates freely with minimal play
	Screw M10 strength 8.8: Tightening torque 30 Nm, Screw M12 strength 5.8: Tightening torque 30 Nm
RECOMMENDED FASTENERS	You can use M10 screws, strength 8.8 and higher, M12 screws, strength 5.8 and higher, according to the steel profiles used, the recommended spacing of the holes and the size of the holes in them