



<b>INTENDED USE</b>	Means of personal fall protection
<b>MATERIAL</b>	Stainless steel 1.4301
<b>CERTIFICATION</b>	According to ČSN EN 795:2013 (1 person) and according to ČSN P CEN/TS 16415:2013 (up to 4 people)
<b>PART OF THE DELIVERY</b>	1× ANCHOR EYE, 1× Nut M16 SELF-LOCKING, 4× Folding anchor Axel Safety M10, Label
<b>NOMINAL HEIGHT OF THE SECURING POINT</b>	200 mm – marking 34-200
	300 mm – marking 34-300
	400 mm – marking 34-400
	500 mm – marking 34-500
	600 mm – marking 34-600
<b>DETERMINING THE HEIGHT OF THE SECURING POINT</b>	Nominal height of the securing point = Height of the roof structure + 100 to 200 mm
<b>MANUFACTURER</b>	Axel Group s.r.o
<b>TIGHTENING TORQUES</b>	Self-locking nut M16: do not tighten, anchor eye rotates freely with minimal play
	Folding anchor M10: tightening torque 30+3Nm
<b>HOLES FOR THE ANCHOR IN THE TRAPEZOIDAL SHEET</b>	To push the anchor through the trapezoidal sheet, it is necessary to drill 4 holes with a diameter of 29 – see assembly instructions